

Datasheet Conveyor Belt



**NITTA CORPORATION
OF HOLLAND**

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
2 MF 207/201
- **Nitta Japan code:**



Construction: 2 plies polyester, rigid

	TOP COVER	INNER LAYER	BOTTOM SIDE	
Material:	PVC	PVC	Impregnated fabric	
Thickness:	0,7		0,1	mm (approx.)
Colour:	Green	Green	Green	
Hardness:	80 Shore A		90 Shore A	
Profile:	-		-	

Total thickness:	3,1	mm (approx.)
Weight:	3,6	kg/m² (approx.)
Max. width:	3000	mm
Belt support:	Sliderbed (Rollers), Flat	

Rating at 1% elongation:	30	N/mm
Advised pretension:	12 - 20	N/mm
Maximum allowable tension:	47	N/mm
Temperature range:	-10 to +80	°C

Minimum pulley diameters:		
Flexing:	120	mm
Backflexing:	120	mm

Special approval: Not applicable

Applications: Agricultural and horticultural industry
Loading and unloading of trucks
Heavy duty applications

Date of issue 01-08-2014-1

Your Partner In Belting Solutions

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nittacorporation.com