

Datasheet Conveyor Belt

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
2 RF 71
- **Nitta Japan code:**



Construction: 2 plies polyester, rigid

	TOP COVER	INNER LAYER	BOTTOM SIDE	
Material:	PVC	PVC	Fabric	
Thickness:	0,7		-	mm (approx.)
Colour:	White	White	-	
Hardness:	65 Shore A		-	
Profile:	-		-	

Total thickness:	2,4		mm (approx.)
Weight:	2,9		kg/m ² (approx.)
Max. width:	3000		mm
Belt support:	Sliderbed (Rollers), Flat		
Rating at 1% elongation:	10		N/mm
Advised pretension:	4 - 7		N/mm
Maximum allowable tension:	20		N/mm
Temperature range:	-10	to +90	°C
Minimum pulley diameters:			
Flexing:	40		mm
Backflexing:	75		mm

Special approval: FDA, 10/2011/EC + amendments

Applications:

- Conveyor belt for the food industry
- Dough handling in bakeries
- Conveying of meat, fish and poultry products
- Oil and grease resistant

Date of issue 22-07-2014-1